

### PARTS LIST - SECTION A

- A. 1/2" Diameter x 12" long pipe (2)
- B. 3/8" Diameter Pipe (2)

### DIAGRAM 1

### GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended to be mounted to a minimum 4" x 1-1/8" deep round outlet box. The box must be directly supported by the building structure.
4. **Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.**

NOTE: The important safeguards and instructions appearing in these instructions are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution, and care are factors, which cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

### SECTION A - FIXTURE ASSEMBLY

NOTE: Before hanging your new light, the fixture must be assembled following these instructions. This fixture uses a telescoping clutch for adjusting the overall hanging length of the fixture. Diagram 2 shows how the clutch works. This section explains how it is assembled.

1. If not already attached, insert the threaded end of the 3/8" diameter pipe (B) into the fixture base. Also attach the swivel (E) the the 1/2" diameter pipe (A). It will be necessary to feed the brown fixture wire and bare copper ground wire through the pipe.
2. Feed the wires through the metal clutch piece (C) making sure the threaded end is up and slide it over the end of the 3/8" diameter pipe (B),
3. Feed the wires through the plastic clutch piece (D) making sure tapered end faces down and slide it over the end of the 3/8" diameter pipe (B).
4. Feed the wires through the 1/2" diameter pipe (A) and then slide each pipe over the 3/8" diameter pipe (B),
5. Now it is possible to set the overall length of the fixture by tightening the metal clutch on to the threads of the 1/2" diameter pipe (A).
6. Trim any excess brown fixture and bare copper wire, making sure to leave at least 12" of wire coming out of the top.
7. After following these step for all two pipes proceed to section B.

### DIAGRAM 2



